

TOP VIEW ANALYZER – TVA100

SPECIFICATIONS



Product group specifications**TVA100****Camera system**

Connection	USB 3.0
Performance	CF03: 150 fps at 1200 × 1200 px 500 fps at 1200 × 350 px 800 fps at 1200 × 200 px 2000 fps at 1200 × 60 px
Dark noise	7 electrons
Dynamic range	73 dB

Optics

Focus	manual
Zoom	6.5× zoom, manual
Field of view	CF03: 1.6 mm × 1.6 mm to 9.1 mm × 9.1 mm
Resolution	CF03: 1.2 μm

Illumination

Type	LED illumination with manual dimmer
------	-------------------------------------

Dosing system

Dosing	electronic pipette
Drop deposition	manual
Syringes, volume	disposable tips (0.1 to 10 μL)

Software

ADVANCE	contact angle surface free energy of solids ¹⁾
---------	--

Measurement specifications**TVA100****Sessile drop**

Result	contact angle
Range	3.5 to 23° (±0.1°), 23 to 75° (±1°)
Models	reflecting curve
Type	static

Surface free energy of solids ¹⁾

Result	surface free energy
Models	equation of state, Zisman, Fowkes, Wu, Owens-Wendt-Rabel-Kaelble, extended Fowkes, acid-base theory

¹⁾ optional

General specifications**TVA100****Sample dimensions**

Maximum sample space 300 mm × ∞ × 50 mm (W × D × H)

EnvironmentOperating temperature 10 to 40 °C
storage: -10 to 70 °C
Humidity without condensation**Instrument dimensions**Footprint 610 mm × 250 mm (W × D)
Height 430 mm
Weight (without accessories) 10 kg**Power supply**Voltage 12 V
Power consumption 40 W**Interfaces**

PC USB 3.0

